

N°630 Recycled Content PP Packaging Tape



PRODUCT DESCRIPTION

- General packaging, and sealing of cardboard cartons (both recycled and virgin board). Suitable for use in benchtop dispensers and hand dispensers.
- Use in applications where strong, durable tape, that is resistance to breakage, is required.
- Provides superior adhesion to steel, plastic, paper and films.



APPLICATION INFORMATION

No. 630 is a biaxially orientated polypropylene (BOPP) tape containing 30% recycled content. The film is coated with a hot melt (synthetic rubber) adhesive. Being a packaging tape, it is suitable for a broad range of purposes including general packaging and carton closing applications. Best used with a dispenser as not hand tearable.



PHYSICAL PROPERTIES

Total Thickness	50µm	Adhesive Type	Hot Melt (synthetic rubber)
Film Thickness	28µm	Elongation	120%
Tensile Strength	75N/25mm	Adhesion to Steel	12N/25mm



AVAILABLE SIZES & COLOURS

* Tolerances: Thickness +/- 2µm; Width +/- 1mm

Standard width	48mm	Colours	Transparent, Brown
Core Size	76mm (3 inch)	Carton Packing	36 rolls
Standard Length	75m		



STORAGE & TEMPERATURE CONDITIONS

Storage	Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight.
Storage Temp	5°C – 50°C
Application Temp	5°C – 60°C

Note: The following technical information and data should be considered representative or typical only.