



# Venhart 754AA Acrylic Tape



## PRODUCT DESCRIPTION

Venhart 754AA tape is a biaxially oriented polypropylene packaging tape with acrylic pressure sensitive adhesive. It has good adhesion, initial viscosity, and retention, high tensile strength, light weight, is non-toxic. Mainly used in medium to heavy duty carton sealing.



## APPLICATION INFORMATION

- Used in packing, sealing, fixing, binding, offices, etc.
- Requires a tape gun or tape dispenser.



## PHYSICAL PROPERTIES

|                         |             |                          |                                       |
|-------------------------|-------------|--------------------------|---------------------------------------|
| <b>Total Thickness</b>  | 65µm        | <b>Adhesive Type</b>     | Hot Melt Pressure Sensitive (Acrylic) |
| <b>Film Thickness</b>   | 42µm        | <b>Elongation</b>        | 100%                                  |
| <b>Tensile Strength</b> | 110N / 25mm | <b>Adhesion to Steel</b> | 7N / 25mm                             |



## AVAILABLE SIZES & COLOURS

\* Tolerances: Thickness +/- 2µm; Width +/- 1mm

| CODE     | SIZE       | ROLLS / CARTON | Colour       |
|----------|------------|----------------|--------------|
| A3217512 | 12mm x 75m | 144            | Brown, Clear |
| A3217518 | 18mm x 75m | 96             |              |
| A32-7524 | 24mm x 75m | 72             |              |
| A32-7536 | 36mm x 75m | 48             |              |
| A32-7548 | 48mm x 75m | 36             |              |
| A3217572 | 72mm x 75m | 24             |              |
| A3217596 | 96mm x 75m | 18             |              |



## STORAGE & TEMPERATURE CONDITIONS

|                         |                                                                                                                                                        |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Storage</b>          | Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. |
| <b>Storage Temp</b>     | -10°C – 60°C                                                                                                                                           |
| <b>Application Temp</b> | 10°C – 40°C                                                                                                                                            |

Note: The following technical information and data should be considered representative or typical only.